

























Safety storage under bench cabinet UB-S-90 model UB90.060.140.2S

light grey (RAL 7035), Interior equipment with 2 x drawer (sheet steel powdercoated), 2 x perforated insert (stainless steel)

Order No. 30401-001-35345 4

Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: body made of powder-coated sheet steel
- User-friendly: drawers remain open in any position, interior of drawers completely visible - access to all containers
- Safe: drawers fitted with earthing wire incl. clamp as standard, seal welded sump, drawers are self-closing in the
- No unauthorised use: drawers lockable with cylinder lock and locking state indicator (red/green)
- Mobile: castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system

Available equipment:

- Second level drawer for optimal utilisation of the inside space when storing small containers
- Perforated insert useable as storage area
- SOFT CLOSE system soft, quiet and complete closure of the drawer













Plenty of space for small containers, optimal utilisation of the inside space when storing small containers



SOFT CLOSE system

No matter how large the force while sliding the drawer – thanks to spring mechanism the drawer closes softly and quietly (optional)

UB90.060.140.2S

Recirculating air filter system

Avoid complex wall breakthroughs and expensive extraction piping.

Especially designed for the lower pressure conditions and volume flows of under bench cabinets.

Further information from page

Order No. 27144 2

(housing unit optional)



Technical data

reeminear data		0230.000.140.23
External dimensions W x D x H	mm	1402 x 574 x 600
Internal dimensions W x D x H	mm	1279 x 452 x 502
Weight without interior equip.	kg	230
Extraction air	DN	50
Air change 10 times	m³/h	3
Diff. pressure (air change 10 times)	Pa	1
Diff. pressure (air change 10 times EK5/A	AK4) Pa	1
Maximum load	kg	300
Distributed load	kg/m²	240
Max. load of drawers	kg	50

Usable storage heights

UB90.060.140.2S


1 mm 465** **2** mm 230***


** without perforated insert *** with second level drawer






Front view Side view **Top view**









Order No. 30401 37066

Available colours:



Order example - how to order correctly









001 005	30401 - 001 - 35349	VVIIII
Model	Information / equipment	
UB90.060.140.2S	without interior equipment, with 2 drawers	
UB90.060.140.UL.2S	without interior equipment, UL/ULC 1275 listed, with 2 drawers	

Body colour Order No. light grey RAL 7035 Light grey RAL 7035 Laboratory white (sim. RAL 9016) 001 <mark>4</mark> 005 **4** laboratory white (sim. RAL 9016) Material Order No. sheet steel powder-coated RAL 7035 35344

Interior equipment packages (can only be ordered in combination with the cabinet)

Left: 1x drawer (V=21.0L)
Right: 1x drawer (V=11.5L)
Left: 1x drawer (V=11.5L)
Left: 1x drawer (V=11.5L)
Left: 1x drawer (V=11.5L), 1x perforated insert
Right: 1x drawer (V=11.5L), 1x perforated insert
Left: 1x drawer (V=20.0L), 1x perforated insert
Left: 1x drawer (V=20.0L), 1x perforated insert
Left: 1x drawer (V=11.5L), 1x perforated insert
Left: 1x drawer (V=20.0L), 1x perforated insert
Left: 1x drawer (V=11.5L), 1x second level drawer
Right: 1x drawer (V=11.5L), 1x second level drawer
Right: 1x drawer (V=10.0L), 1x perforated insert, 1x second level drawer
Right: 1x drawer (V=11.5L), 1x perforated insert, 1x second level drawer
Right: 1x drawer (V=20.0L), 1x perforated insert, 1x second level drawer
Left: 1x drawer (V=20.0L), 1x perforated insert, 1x second level drawer
Left: 1x drawer (V=20.0L), 1x perforated insert, 1x second level drawer
Right: 1x drawer (V=11.5L), 1x perforated insert, 1x second level drawer 35349 6 stainless steel sheet steel powder-coated RAL 7035, stainless steel 35345 2 35350 6 stainless steel 35348 2 sheet steel powder-coated RAL 7035 35353 6 stainless steel sheet steel powder-coated RAL 7035, stainless steel 35346 2 25251

Right: 1x drawer (V=20.0L), 1x perforated insert, 1x second level of						35351 👩	
Interior equipment	Material	W x D x H (mm)	1)	2	3)	Order No.	
Left side							
Second level drawer for cabinet/compartment width 89 cm	sheet steel powder-coated RAL 7035	743 x 418 x 45*	25.00	5.50	5.00	30406 🕗	
Second level drawer for cabinet/compartment width 89 cm	stainless steel	743 x 418 x 45*	25.00	5.50	5.00	30408 2	
Perforated insert	stainless steel	717 x 436 x 9	75.00			9974 2	
Sump inliner for second level drawer (1 pc, recom. 2 pcs)	PE black	734 x 199 x 20*		2.50	2.27	10907 2	
Sump inliner for shelf	PP grey	653 x 406 x 88*		21.50	19.55	9707 2	
Anti-slip rubber mat	black	720 x 438 x 1				8700 2	
Right side							
Second level drawer for cabinet/compartment width 59 cm	sheet steel powder-coated RAL 7035	443 x 418 x 45*	25.00	3.00	2.73	30407 2	
Second level drawer for cabinet/compartment width 59 cm	stainless steel	443 x 418 x 45*	25.00	3.00	2.73	30409 2	
Perforated insert	stainless steel	417 x 436 x 9	75.00			9975 2	
Sump inliner for second level drawer (1 pc, recom. 2 pcs)	PE black	434 x 199 x 20*		1.50	1.36	10904 2	
Sump inliner	PP grey	353 x 406 x 88*		11.50	10.45	9706 🕗	
Anti-slip rubber mat	black	420 x 438 x 1				8698 2	
Accessories for both sides							
Pipe lead-through	sheet steel powder-coated RAL 7035	182 x 104 x 48				30035 🕗	
Castors with plinth height = 30 mm	sheet steel powder-coated RAL 7015					31359 2	
Dattle reals for 15 hettles with 0.70 mm	shoot stool nounder control DAL 700F	210 v 440 v 20				7000	

Pipe lead-through	sheet steel powder-coated RAL 7035	182 x 104 x 48	30035 🕗
Castors with plinth height = 30 mm	sheet steel powder-coated RAL 7015		31359 🕗
Bottle rack for 15 bottles with Ø 70 mm	sheet steel powder-coated RAL 7035	210 x 440 x 30	7603 2
Bottle rack for 32 bottles with Ø 40 mm	sheet steel powder-coated RAL 7035	210 x 440 x 30	7602 🕗
Bottle rack for 8 bottles with Ø 90 mm	sheet steel powder-coated RAL 7035	210 x 440 x 30	7604 🕗
Document holder DIN A5	polystyrene		30793 2
SOFT-CLOSE			33982 🕗
Connection eccentric adapter DN50 to DN75	PP		32165 🕗

Ventilation	Order No.
Extraction module with exhaust air monitoring for wall mounting, for under bench cabinets	24315 🕗
Recirculating air filter system with exhaust air monitoring, for under bench cabinets	27144 🕗
Adapter as separate housing unit for lateral mounting	26885 2

^{*} usable storage space W x D (mm)
1) load capacity (kg), 2) retention capacity (ltr.), 3) maximum container volume in the cabinet (ltr.)

