



JAW CRUSHER BB 50

The compact benchtop model

The BB 50 is the smallest model of the RETSCH jaw crusher series and has been specially designed for sample preparation in the laboratory. The compact machine fits on any laboratory bench and offers safe and convenient handling.

The RETSCH jaw crusher series is available in 8 different sizes. Throughput and final fineness depend on the crusher type, selected gap width and breaking properties of the sample material.

Robust design, simple handling and cleaning are the features of the RETSCH jaw crusher models. Small amounts of sample are processed batchwise; for larger amounts the crushers can be operated continuously.





[Click to view video](#)

Product Video

POWERFUL & COMPACT

- High crushing efficiency, feed sizes up to 40 mm can be crushed to 0.5 mm
- Removable jaw for easy cleaning
- Adjustable speed allows adaptation to sample characteristics
- Wear compensation with zero-point adjustment
- Convenient operating keypad with digital display
- Memory for gap width setting



Small, powerful benchtop unit

JAW CRUSHER BB 50

SUPERIORITY IN DETAIL

The BB 50 is designed for efficient and convenient size reduction. The variable speed can be set between 550 and 950 min^{-1} to adapt the crushing process to sample requirements. The possibility to reverse the rotating direction is helpful if too much sample material has been fed to the crusher causing it to block. The simple push of a button restarts the process. Due to permanently lubricated bearings and its solid design, the BB 50 jaw crusher is virtually maintenance-free.



Fold-back hopper can be removed for easy access



Digital speed setting and display of gap width




Large collection receptacle (3 l) with optional lid

JAW CRUSHER BB 50

ZERO POINT ADJUSTMENT

An advantage of the jaw crusher BB 50 is the so-called zero point adjustment. Sooner or later, the breaking jaws will show signs of wear which will affect the reproducibility of the size reduction process. This effect can be compensated by adjusting the zero point. A sign in the display indicates if the jaws need to be replaced altogether, thus helping to avoid damages to the crusher.



[Click to view video](#)

JAW CRUSHER BB 50

EASY OPERATION & CLEANING

Working with the BB 50 jaw crusher is easy and safe. The large, clearly structured operating panel allows for digital display of parameters such as gap width and speed. The sample material is conveniently fed to the crusher via the large hopper equipped with splash-back protection.

For easy cleaning the fold-back hopper and crusher arm can be removed without using tools. The user can also exchange the breaking jaws if the crusher needs to be converted for different applications.




[Click to view video](#)

FOR SAFE AND EFFICIENT CRUSHING PROCESSES

ACCESSORIES FOR THE JAW CRUSHER BB 50

Breaking jaws and wearing plates are available in five different materials to be selected depending on the sample and the analysis to be carried out:

- | manganese steel
- | stainless steel
- | tungsten carbide
- | zirconium oxide
- | steel for heavy-metal free grinding



The optional lid for the collecting receptacle of the jaw crusher ensures that the fine residues from previous samples fall on the lid and not into the receptacle which helps to avoid cross contaminations.

JAW CRUSHER BB 50

TYPICAL SAMPLE MATERIALS

RETSCH's powerful jaw crushers are ideally suited for preliminary crushing of construction materials, ores, granite, oxide ceramics, quartz, slag, silicon, coal, tungsten alloys, cement clinker, etc.



concrete



jade



glass



coal

To find the best solution for your sample preparation task, visit our application database.

JAW CRUSHER BB 50

FUNCTIONAL PRINCIPLE

The Jaw Crusher BB 50 is a robust and powerful forced-feed crusher. The feed material passes through the no-rebound hopper and enters the crushing chamber.

Size reduction in the Jaw Crusher takes place in the wedgeshaped area between the fixed crushing arm and one moved by an eccentric drive shaft. The elliptical motion crushes the sample which then falls under gravity.

As soon as the sample is smaller than the discharge gap width, it falls into a removable collector. The continuous gap width setting with digital display ensure optimal size reduction in accordance with the set gap width value.



[Click to view video](#)

JAW CRUSHER BB 50

TECHNICAL DATA

Applications	coarse and pre-crushing
Field of application	agriculture, biology, construction materials, geology / metallurgy, glass / ceramics, medicine / pharmaceuticals
Feed material	medium-hard, hard, brittle, tough
Size reduction principle	pressure
Material feed size*	< 40 mm
Final fineness*	< 0.5 mm
Throughput*	3 l/batch
Material of grinding tools	manganese steel, stainless steel, tungsten carbide, zirconium oxide, steel 1.1750 (for heavy-metal free grinding)
Jaw width	45 x 59 mm
Gap width setting	0 - 11 mm in increments 0.1 mm
Gap width display	digital
Zero point adjustment	Yes
Reverse rotating direction	Yes
Hinged hopper	Yes
Dust extraction unit	already dust-tight
Central lubrication	lifetime lubrication by manufacturer
Process line version	process line use is possible by removing drawer
Collector capacity	3 l
Drive	3-phase motor with frequency converter
Drive power	1.1 kW
Electrical supply data	different voltages
Power connection	1-phase
Protection code	IP 20 / IP 00 at ventilation slots
W x H x D closed	420 x 460 x 560 mm
Net weight	~ 79 kg
Standards	CE

*depending on feed material and instrument configuration/settings

www.retsch.com/bb50

ORDER DATA

JAW CRUSHER BB 50

Jaw Crusher BB 50 complete with breaking jaws and wearing plates

			breaking jaws / wearing plates	
20.062.0001		BB 50	200–240 V, 50/60 Hz	manganese steel / stainless steel
20.062.0002		BB 50	200–240 V, 50/60 Hz	stainless steel / stainless steel
20.062.0009		BB 50	200–240 V, 50/60 Hz	stainless steel / stainless steel
20.062.0003		BB 50	200–240 V, 50/60 Hz	tungsten carbide / tungsten carbide
20.062.0004		BB 50	200–240 V, 50/60 Hz	zirconium oxide / zirconium oxide
20.062.0005		BB 50	200–240 V, 50/60 Hz	steel 1.1750 / steel 1.0344, for grinding without heavy-metal contamination

CYCLONE FOR BB 50

CYCLONE SET WITH HOLDER, CONNECTING ELEMENT, LID WITH CONNECTOR FOR VACUUM CLEANER AND SAMPLE OUTLET
(PLEASE ORDER CASSETTE WITH OUTLET SEPARATELY)

22.935.0038	Cyclone set with sample bottles 0.25 and 0.5 liters
03.183.0140	Cassette with outlet for use with cyclone
22.748.0017	Industrial vacuum cleaner Attix, 230 V, 50/60 Hz

ACCESSORIES JAW CRUSHER BB 50

BREAKING JAWS BB 50

22.048.0014		Breaking jaws manganese steel 1 pair
-------------	---	--

22.048.0012		Breaking jaws stainless steel 1 pair
22.048.0023		Breaking jaws stainless steel, waved 1 pair
22.048.0010		Breaking jaws tungsten carbide 1 pair
22.048.0011		Breaking jaws zirconium oxide 1 pair
22.048.0016		Breaking jaws steel 1.1750 1 pair, for grinding without heavy-metal contamination

WEARING PLATES BB 50		
22.711.0015		Wearing plates stainless steel 1 pair
22.711.0016		Wearing plates tungsten carbide 1 pair
22.711.0017		Wearing plates zirconium oxide 1 pair
22.711.0018		Wearing plates steel 1.0344 1 pair, for grinding without heavy-metal contamination

FURTHER ACCESSORIES BB 50		
03.050.0437		Cover lid for collecting receptacle

05.242.0038



V-belt, 1 piece

22.825.0005



Carry handles, 1 pair