297352Q

Aluminium telescopic waterfed handle w/Q coupling, 1600 mm, Black



This professional telescopic water-fed handle (1600–2840 mm) has an insulated sleeve for a comfortable grip and a quick-release hose connector. Maximum water pressure, 6 bars.

Technical Data

Item Number 297352Q **Material** Anodised Aluminium Polypropylene Chromium-plated brass Meets the REACH Regulation (EC) No. 1907/2006 Yes ** **Box Quantity** 5 Pcs. Quantity per Pallet (80 x 120 x 200 cm) 500 Pcs **Quantity Per Layer (Pallet)** 25 Pcs. **Box Length** 1650 mm **Box Width** 140 mm **Box Height** 85 mm **Product Diameter** 31 mm Length 1600 mm Width 31 mm Height 31 mm Max. Length 2780 mm **Gross Weight** 1,1 kg **Net Weight** 1,02 kg **Cubik metre** 0,0015 M3 Max. bars pressure 6 Bar 50 °C Max usage temperature (non food contact) Min. pH-value in usage concentration 4 pH Max. pH-value in Usage Concentration 11 pH **Gtin-13 Number** 5705022973022 **GTIN-14 Number (Box quantity)** 15705022973029 **Customs Tariff No.** 76082020 **Country of origin** Denmark

^{**} Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead.