



LKPV 1423
MediLine



LKPV 1420
MediLine



Gross / net capacity	1397 / 980 litre
Exterior dimensions in mm (w / d / h)	1430 / 830 / 2160
Interior dimensions in mm (w / d / h)	1236 / 650 / 1500
Energy consumption in 365 days ¹	820 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	515 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	3.8 °C / 3.9 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Adjustable shelves	8
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	1236 / 640
Shelf loading	60 kg
Castors	castors with brake at the front, castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	left hand / right hand
Gross / net weight	267 / 224 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590639
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



LKPV 8420
MediLine



LKPV 6523
MediLine



LKPV 6520
MediLine



LKPV 6527
MediLine



Gross / net capacity	855 / 629 litre
Exterior dimensions in mm (w / d / h)	790 / 980 / 2160
Interior dimensions in mm (w / d / h)	620 / 850 / 1550
Energy consumption in 365 days ¹	603 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	430 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	2.1 °C / 1.8 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	620 / 800
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	175 / 145 kg
Accessories	
Shelf, plastic-coated	7113643
U-shaped trayslide, right	9005089
U-shaped trayslide, left	9005077
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	617 / 430 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1500
Energy consumption in 365 days ¹	571 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	345 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	2.0 °C / 1.6 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	164 / 138 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	602 / 430 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1550
Energy consumption in 365 days ¹	497 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	300 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	1.8 °C / 1.0 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	154 / 128 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	598 / 429 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1550
Energy consumption in 365 days ¹	688 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	345 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	1.8 °C / 1.0 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	155 / 130 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.