



Vertical LED lighting

Vertical LED lighting provides optimal illumination of the interior over the entire height of the appliance. Thanks to the perfect overview on all levels, the required substance is immediately at hand, the door can be quickly closed again, and the interior temperature remains stable. This saves you time looking for things – and above all energy costs.



Pharmacy drawers

Optimal overview, easy access, high temperature stability: the practical organisational system made of cold-conducting aluminium comes with a transparent front, perforated base, flexible dividing walls and a ¾-extension drawer. Medicines, vaccines and other items can be quickly found – and the door closed again with minimal loss of cold air.

Pharmaceutical refrigerators compliant with DIN 13277 with organisational system



HMFvh 5511
ver. H63 Perfection



HMFvh 5501
ver. H63 Perfection



HMFvh 4011
ver. H63 Perfection



HMFvh 4001
ver. H63 Perfection



Gross / net capacity	
Exterior dimensions in mm (w / d / h)	
Interior dimensions in mm (w / d / h)	
Energy consumption in 365 days¹	
Ambient temperature range	
Refrigerant	
Sound power level	
Voltage / Connection rating	
Cooling system / Defrost	
Temperature range	
Gradient² / max. fluctuation³	
External cabinet finish	
Door material	
Internal liner material	
Type of control	
Power failure alarm	
Fault: warning signal	
Volt-free alarm contact	
Connectivity type / Connectivity solution	
Interface / Data logger	
Interior light	
Number of shelves / Adjustable shelves	
Number of drawers	
Shelf material	
Usable shelf area in mm (w / d)	
Shelf loading / device	
Castors	
Handle	
Type of lock	
Door hinges	
Gross / net weight	
Accessories	
Shelf, plastic-coated	
Base grid / Glass shelf	
Perforated metal shelf / Scanner rail	
Castors Ø 80 mm / Ø 100 mm	
Adjustable feet, 90 – 120 mm / 150 – 180 mm	
Side-by-Side set	
Additional remote controls	
Digital input for electronic lock	

588 / 355 litre
747 / 769 / 1793
556 / 460 / 1460
400 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
3.1 °C / 2.6 °C
steel / white
glass
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
Vertical LED light strip recessed in left wall with separate switch
1 / 1
7
wire shelves plastic-coated
556 / 460
50 kg / 300 kg
castors with brake at the front, fixed castors at the rear
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
101 / 97 kg
7113310
7113314 / 9291929
- / 7435210
9086926 / -
9080022 / 9086924
on request
6123395
9086958

558 / 355 litre
747 / 769 / 1793
556 / 460 / 1460
171 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
2.8 °C / 2.3 °C
steel / white
steel
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
LED lighting column, left
1 / 1
7
wire shelves plastic-coated
556 / 460
50 kg / 300 kg
castors with brake at the front, fixed castors at the rear
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
106 / 100 kg
7113310
7113314 / 9291929
- / 7435210
9086926 / -
9080022 / 9086924
on request
6123395
9086958

420 / 235 litre
597 / 654 / 1884
406 / 370 / 1660
409 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
4.1 °C / 2.2 °C
steel / white
glass
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
Vertical LED light strip recessed in left wall with separate switch
1 / 1
8
wire shelves plastic-coated
406 / 370
50 kg / 225 kg
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
82 / 69 kg
7113308
7113312 / 9293493
9029022 / 7435208
9080022 / 9086924
on request
6123395
9086958

394 / 235 litre
597 / 654 / 1884
406 / 370 / 1660
172 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
4.9 °C / 2.6 °C
steel / white
steel
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
LED lighting column, left
1 / 1
8
wire shelves plastic-coated
406 / 370
50 kg / 225 kg
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
69 / 64.5 kg
7113308
7113312 / 9293493
9029022 / 7435208
9086926 / 9080023
9080022 / 9086924
on request
6123395
9086958

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.