



EMERGENCY SHOWER & EYEWASH

The most popular combination unit of drench shower cum eyewash for any industry, this unit is highly recommended in all accident / contamination prone areas.

GENERAL FEATURES

- **Shower and Eyewash Bowl:**
280mm (11") dia bowls are injection moulded in chemical resistant ABS in bright yellow.
- **Eyewash Assembly:**
Stainless steel with ABS sprayhead with instant flip-open protective dust-covers. The built-in automatic pressure compensating valve assures safe steady flow under varying water supply conditions. Sprayheads also include a filter to protect users against particles from the water flow which may be damaging to the eyes and face.
- **Control Valve:**
1" fast-action stainless steel(316) ball valve is used for the shower assembly with a stainless steel pull rod. 1/2" fast-action stainless steel(316) ball valve is used for the eyewash assembly with a stainless steel push plate.
- **Pedestal:**
250mm (10") dia aluminium pedestal with 3 mounting holes for 9mm bolts. Pedestal is epoxy powder coated in bright yellow.
- **Pipe and Fitting:**
1" Galvanised Iron pipe epoxy powder coated in bright yellow.
- **Waste:**
1" IPS.
- **Certified to:**
*ANSI / SEAZ358.81 - 2009
AS 4775-2007*
- **Pipe Threads:**
Pipe threads in accordance to BS supplied as standard.
- **Water Supply:**
1" IPS.
- **Signage:**
Drench Shower and Eyewash.

