SafeOne, back flows prevention, 1/2"





For use with foam sprayers 9300, 9301, 9305 and 9306 as protection against chemical backflow into the water supply system.

Technical Data

Item Number	9340
Couplings Size	1/2 "
Approval	
Material	Chromium-plated brass
Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
FDA compliant raw material (CFR 21)	No
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
Use of phthalates and bisphenol A	No
Box Quantity	8 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	4104 Pcs
Quantity Per Layer (Pallet)	1 Pcs.
Box Length	250 mm
Box Width	175 mm
Box Height	70 mm
Length	135 mm
Width	30 mm
Height	30 mm
Gross Weight	0,44 kg
Net Weight	0,43 kg
Cubik metre	0,0001 M3
Recommended sterilisation temperature (Autoclave)	60 °C
Max. cleaning temperature (Dishwasher)	60 °C
Max usage temperature (non food contact)	60 °C
Min. usage temperature ³	5 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Min. Bars pressure	10 Bar
Max. bars pressure	25 Bar
Gtin-13 Number	5705020093401
GTIN-14 Number (Box quantity)	15705020093408
Customs Tariff No.	84818099
Country of origin	Denmark

^{**} Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead.