



SRFvg 5511
Performance



SRFvg 5501
Performance



SRFvg 4011
Performance



SRFvg 4001
Performance



SRFvg 3511
Performance



SRFvg 3501
Performance



| | |
|--|--|
| Gross / net capacity | 588 / 440 litre |
| Exterior dimensions in mm (w / d / h) | 747 / 769 / 1684 |
| Interior dimensions in mm (w / d / h) | 606 / 536 / 1442 |
| Energy consumption in 365 days¹ | 433 kWh |
| Ambient temperature range | +10°C to +35°C |
| Heat output | 542 kJ/h |
| Refrigerant | R 600a |
| Sound power level | 49 dB(A) |
| Voltage / Connection rating | 220 - 240V~ / 2.0 A |
| Cooling system / Defrost | forced-air / automatic |
| Temperature range | +3°C to +16°C |
| Gradient² / max. fluctuation³ | 3.8°C / 3.2°C |
| External cabinet finish | steel / white |
| Door material | glass |
| Internal liner material | commercial grade moulded polystyrol |
| Type of control | monochrome display, touch buttons |
| Power failure alarm | when mains power return |
| Fault: warning signal | visual and audible |
| Volt-free alarm contact | yes |
| Connectivity type / Connectivity solution | SmartModule / Retrofittable |
| Interface | WiFi/LAN (optional) |
| Interior light | LED ceiling light strip with separate switch |
| Adjustable shelves / Shelf material | 5 / wire shelves plastic-coated |
| Usable shelf area in mm (w / d) | 606 / 536 |
| Shelf loading / device | 60 kg / 300 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Access ports | 1 x Ø 10 mm |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross / net weight | 106 / 96 kg |
| Accessories | |
| Shelf, plastic-coated | 7113310 |
| Base grid | 7113314 |
| Glass shelf | 9291929 |
| Perforated metal shelf | |
| Scanner rail | 7435210 |
| Castors Ø 80 mm / Ø 100 mm | 9086926 / 9080023 |
| Adjustable feet, 90 - 120 mm / 150 - 180 mm | 9080022 / 9086924 |
| Evaporator cover | |
| Additional lock barrels (up to 5) | on request |
| Side-by-Side set | on request |
| SmartModule | 6145269 |

| | |
|--|--|
| Gross / net capacity | 558 / 441 litre |
| Exterior dimensions in mm (w / d / h) | 747 / 769 / 1684 |
| Interior dimensions in mm (w / d / h) | 606 / 536 / 1460 |
| Energy consumption in 365 days¹ | 250 kWh |
| Ambient temperature range | +10°C to +35°C |
| Heat output | 317 kJ/h |
| Refrigerant | R 600a |
| Sound power level | 49 dB(A) |
| Voltage / Connection rating | 220 - 240V~ / 2.0 A |
| Cooling system / Defrost | forced-air / automatic |
| Temperature range | +3°C to +16°C |
| Gradient² / max. fluctuation³ | 3.9°C / 3.0°C |
| External cabinet finish | steel / white |
| Door material | steel |
| Internal liner material | commercial grade moulded polystyrol |
| Type of control | monochrome display, touch buttons |
| Power failure alarm | when mains power return |
| Fault: warning signal | visual and audible |
| Volt-free alarm contact | yes |
| Connectivity type / Connectivity solution | SmartModule / Retrofittable |
| Interface | WiFi/LAN (optional) |
| Interior light | LED ceiling light strip with separate switch |
| Adjustable shelves / Shelf material | 5 / wire shelves plastic-coated |
| Usable shelf area in mm (w / d) | 606 / 536 |
| Shelf loading / device | 60 kg / 300 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Access ports | 1 x Ø 10 mm |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross / net weight | 87 / 80 kg |

| | |
|--|--|
| Gross / net capacity | 420 / 297 litre |
| Exterior dimensions in mm (w / d / h) | 597 / 654 / 1884 |
| Interior dimensions in mm (w / d / h) | 460 / 423 / 1642 |
| Energy consumption in 365 days¹ | 431 kWh |
| Ambient temperature range | +10°C to +35°C |
| Heat output | 542 kJ/h |
| Refrigerant | R 600a |
| Sound power level | 49 dB(A) |
| Voltage / Connection rating | 220 - 240V~ / 2.0 A |
| Cooling system / Defrost | forced-air / automatic |
| Temperature range | +3°C to +16°C |
| Gradient² / max. fluctuation³ | 5.9°C / 3.4°C |
| External cabinet finish | steel / white |
| Door material | glass |
| Internal liner material | commercial grade moulded polystyrol |
| Type of control | monochrome display, touch buttons |
| Power failure alarm | when mains power return |
| Fault: warning signal | visual and audible |
| Volt-free alarm contact | yes |
| Connectivity type / Connectivity solution | SmartModule / Retrofittable |
| Interface | WiFi/LAN (optional) |
| Interior light | LED ceiling light strip with separate switch |
| Adjustable shelves / Shelf material | 5 / wire shelves plastic-coated |
| Usable shelf area in mm (w / d) | 460 / 423 |
| Shelf loading / device | 45 kg / 225 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Access ports | 1 x Ø 10 mm |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross / net weight | 89 / 82 kg |

| | |
|--|--|
| Gross / net capacity | 394 / 298 litre |
| Exterior dimensions in mm (w / d / h) | 597 / 654 / 1884 |
| Interior dimensions in mm (w / d / h) | 460 / 423 / 1660 |
| Energy consumption in 365 days¹ | 245 kWh |
| Ambient temperature range | +10°C to +35°C |
| Heat output | 321 kJ/h |
| Refrigerant | R 600a |
| Sound power level | 49 dB(A) |
| Voltage / Connection rating | 220 - 240V~ / 2.0 A |
| Cooling system / Defrost | forced-air / automatic |
| Temperature range | +3°C to +16°C |
| Gradient² / max. fluctuation³ | 4.6°C / 2.2°C |
| External cabinet finish | steel / white |
| Door material | steel |
| Internal liner material | commercial grade moulded polystyrol |
| Type of control | monochrome display, touch buttons |
| Power failure alarm | when mains power return |
| Fault: warning signal | visual and audible |
| Volt-free alarm contact | yes |
| Connectivity type / Connectivity solution | SmartModule / Retrofittable |
| Interface | WiFi/LAN (optional) |
| Interior light | LED ceiling light strip with separate switch |
| Adjustable shelves / Shelf material | 5 / wire shelves plastic-coated |
| Usable shelf area in mm (w / d) | 460 / 423 |
| Shelf loading / device | 45 kg / 225 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Access ports | 1 x Ø 10 mm |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross / net weight | 71 / 66 kg |

| | |
|--|--|
| Gross / net capacity | 367 / 260 litre |
| Exterior dimensions in mm (w / d / h) | 597 / 654 / 1684 |
| Interior dimensions in mm (w / d / h) | 460 / 423 / 1442 |
| Energy consumption in 365 days¹ | 393 kWh |
| Ambient temperature range | +10°C to +35°C |
| Heat output | 471 kJ/h |
| Refrigerant | R 600a |
| Sound power level | 48 dB(A) |
| Voltage / Connection rating | 220 - 240V~ / 2.0 A |
| Cooling system / Defrost | forced-air / automatic |
| Temperature range | +3°C to +16°C |
| Gradient² / max. fluctuation³ | 3.6°C / 3.2°C |
| External cabinet finish | steel / white |
| Door material | glass |
| Internal liner material | commercial grade moulded polystyrol |
| Type of control | monochrome display, touch buttons |
| Power failure alarm | when mains power return |
| Fault: warning signal | visual and audible |
| Volt-free alarm contact | yes |
| Connectivity type / Connectivity solution | SmartModule / Retrofittable |
| Interface | WiFi/LAN (optional) |
| Interior light | LED ceiling light strip with separate switch |
| Adjustable shelves / Shelf material | 4 / wire shelves plastic-coated |
| Usable shelf area in mm (w / d) | 460 / 423 |
| Shelf loading / device | 45 kg / 180 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Access ports | 1 x Ø 10 mm |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross / net weight | 82 / 76 kg |

| | |
|--|--|
| Gross / net capacity | 344 / 261 litre |
| Exterior dimensions in mm (w / d / h) | 597 / 654 / 1684 |
| Interior dimensions in mm (w / d / h) | 460 / 423 / 1460 |
| Energy consumption in 365 days¹ | 226 kWh |
| Ambient temperature range | +10°C to +35°C |
| Heat output | 288 kJ/h |
| Refrigerant | R 600a |
| Sound power level | 48 dB(A) |
| Voltage / Connection rating | 220 - 240V~ / 2.0 A |
| Cooling system / Defrost | forced-air / automatic |
| Temperature range | +3°C to +16°C |
| Gradient² / max. fluctuation³ | 5.0°C / 3.1°C |
| External cabinet finish | steel / white |
| Door material | steel |
| Internal liner material | commercial grade moulded polystyrol |
| Type of control | monochrome display, touch buttons |
| Power failure alarm | when mains power return |
| Fault: warning signal | visual and audible |
| Volt-free alarm contact | yes |
| Connectivity type / Connectivity solution | SmartModule / Retrofittable |
| Interface | WiFi/LAN (optional) |
| Interior light | LED ceiling light strip with separate switch |
| Adjustable shelves / Shelf material | 4 / wire shelves plastic-coated |
| Usable shelf area in mm (w / d) | 460 / 423 |
| Shelf loading / device | 45 kg / 180 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Access ports | 1 x Ø 10 mm |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross / net weight | 66 / 60 kg |

| | |
|--|-------------------|
| Gross / net capacity | 7113308 |
| Shelf, plastic-coated | 7113310 |
| Base grid | 7113314 |
| Glass shelf | 9293493 |
| Perforated metal shelf | 9029022 |
| Scanner rail | 7435208 |
| Castors Ø 80 mm / Ø 100 mm | 9086926 / 9080023 |
| Adjustable feet, 90 - 120 mm / 150 - 180 mm | 9080022 / 9086924 |
| Evaporator cover | 9803590 |
| Additional lock barrels (up to 5) | on request |
| Side-by-Side set | on request |
| SmartModule | 6145269 |

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.