



**LGPv 1420**  
MediLine



**LGPv 8420**  
MediLine



**LGPv 6520**  
MediLine



**LGPv 6527**  
MediLine



<b>Gross / net capacity</b>	1366 / 980 litre
<b>Exterior dimensions in mm (w / d / h)</b>	1430 / 830 / 2160
<b>Interior dimensions in mm (w / d / h)</b>	1236 / 650 / 1550
<b>Energy consumption in 365 days<sup>1</sup></b>	2654 kWh
<b>Ambient temperature range</b>	+10 °C to +40 °C
<b>Refrigerant</b>	R 290
<b>Sound power level</b>	60 dB(A)
<b>Voltage / Connection rating</b>	220 - 240V~ / 4.0 A
<b>Cooling system</b>	forced-air
<b>Defrost</b>	automatic
<b>Temperature range</b>	-9 °C to -26 °C
<b>Gradient<sup>3</sup> / max. fluctuation<sup>4</sup></b>	4.3 °C / 6.7 °C
<b>External cabinet finish</b>	steel / white
<b>Door material</b>	steel
<b>Internal liner material</b>	304-grade stainless steel
<b>Type of control</b>	LED 7-segment display with buttons
<b>Power failure alarm</b>	immediately upon power failure for 72 hrs
<b>Fault: warning signal</b>	visual and audible
<b>Volt-free alarm contact</b>	yes
<b>Connectivity type</b>	SmartCoolingHub
<b>Connectivity solution</b>	Retrofittable
<b>Interface</b>	RS485
<b>Adjustable shelves</b>	8
<b>Shelf material</b>	wire shelves plastic-coated
<b>Usable shelf area in mm (w / d)</b>	1236 / 640
<b>Shelf loading</b>	60 kg
<b>Castors</b>	castors with brake at the front, castors at the rear
<b>Handle</b>	full-length integrated handle
<b>Type of lock</b>	mechanical
<b>Door hinges</b>	left hand / right hand
<b>Gross / net weight</b>	254 / 209 kg
<b>Accessories</b>	
<b>Shelf, plastic-coated</b>	7112393
<b>U-shaped trayslide, right</b>	9001761
<b>U-shaped trayslide, left</b>	9001757
<b>Foot pedal opener</b>	9590639
<b>SmartCoolingHub</b>	6125784
<b>Product temperature sensor</b>	9590407
<b>Side-by-Side set</b>	9901947

<b>Gross / net capacity</b>	855 / 629 litre
<b>Exterior dimensions in mm (w / d / h)</b>	790 / 980 / 2160
<b>Interior dimensions in mm (w / d / h)</b>	620 / 850 / 1550
<b>Energy consumption in 365 days<sup>1</sup></b>	1739 kWh
<b>Ambient temperature range</b>	+10 °C to +40 °C
<b>Refrigerant</b>	R 290
<b>Sound power level</b>	60 dB(A)
<b>Voltage / Connection rating</b>	220 - 240V~ / 4.0 A
<b>Cooling system</b>	forced-air
<b>Defrost</b>	automatic
<b>Temperature range</b>	-9 °C to -35 °C <sup>2</sup>
<b>Gradient<sup>3</sup> / max. fluctuation<sup>4</sup></b>	4.5 °C / 5.7 °C
<b>External cabinet finish</b>	steel / white
<b>Door material</b>	steel
<b>Internal liner material</b>	304-grade stainless steel
<b>Type of control</b>	LED 7-segment display with buttons
<b>Power failure alarm</b>	immediately upon power failure for 72 hrs
<b>Fault: warning signal</b>	visual and audible
<b>Volt-free alarm contact</b>	yes
<b>Connectivity type</b>	SmartCoolingHub
<b>Connectivity solution</b>	Retrofittable
<b>Interface</b>	RS485
<b>Adjustable shelves</b>	4
<b>Shelf material</b>	wire shelves plastic-coated
<b>Usable shelf area in mm (w / d)</b>	620 / 800
<b>Shelf loading</b>	60 kg
<b>Castors</b>	castors with brake at the front, fixed castors at the rear
<b>Handle</b>	full-length integrated handle
<b>Type of lock</b>	mechanical
<b>Door hinges</b>	right, reversible on site
<b>Gross / net weight</b>	182 / 150 kg
<b>Accessories</b>	
<b>Shelf, plastic-coated</b>	7113643
<b>U-shaped trayslide, right</b>	9005089
<b>U-shaped trayslide, left</b>	9005077
<b>Foot pedal opener</b>	9590659
<b>SmartCoolingHub</b>	6125784
<b>Product temperature sensor</b>	9590407
<b>Side-by-Side set</b>	9901947

<b>Gross / net capacity</b>	602 / 430 litre
<b>Exterior dimensions in mm (w / d / h)</b>	700 / 830 / 2160
<b>Interior dimensions in mm (w / d / h)</b>	533 / 650 / 1550
<b>Energy consumption in 365 days<sup>1</sup></b>	1367 kWh
<b>Ambient temperature range</b>	+10 °C to +40 °C
<b>Refrigerant</b>	R 290
<b>Sound power level</b>	60 dB(A)
<b>Voltage / Connection rating</b>	220 - 240V~ / 4.0 A
<b>Cooling system</b>	forced-air
<b>Defrost</b>	automatic
<b>Temperature range</b>	-9 °C to -35 °C <sup>2</sup>
<b>Gradient<sup>3</sup> / max. fluctuation<sup>4</sup></b>	2.9 °C / 3.6 °C
<b>External cabinet finish</b>	steel / white
<b>Door material</b>	steel
<b>Internal liner material</b>	304-grade stainless steel
<b>Type of control</b>	LED 7-segment display with buttons
<b>Power failure alarm</b>	immediately upon power failure for 72 hrs
<b>Fault: warning signal</b>	visual and audible
<b>Volt-free alarm contact</b>	yes
<b>Connectivity type</b>	SmartCoolingHub
<b>Connectivity solution</b>	Retrofittable
<b>Interface</b>	RS485
<b>Adjustable shelves</b>	4
<b>Shelf material</b>	wire shelves plastic-coated
<b>Usable shelf area in mm (w / d)</b>	533 / 650
<b>Shelf loading</b>	60 kg
<b>Castors</b>	castors with brake at the front, fixed castors at the rear
<b>Handle</b>	full-length integrated handle
<b>Type of lock</b>	mechanical
<b>Door hinges</b>	right, reversible on site
<b>Gross / net weight</b>	162 / 136 kg
<b>Accessories</b>	
<b>Shelf, plastic-coated</b>	7112393
<b>U-shaped trayslide, right</b>	9001761
<b>U-shaped trayslide, left</b>	9001757
<b>Foot pedal opener</b>	9590659
<b>SmartCoolingHub</b>	6125784
<b>Product temperature sensor</b>	9590407
<b>Side-by-Side set</b>	9901947

<b>Gross / net capacity</b>	598 / 429 litre
<b>Exterior dimensions in mm (w / d / h)</b>	700 / 830 / 2160
<b>Interior dimensions in mm (w / d / h)</b>	533 / 650 / 1550
<b>Energy consumption in 365 days<sup>1</sup></b>	2019 kWh
<b>Ambient temperature range</b>	+10 °C to +40 °C
<b>Refrigerant</b>	R 290
<b>Sound power level</b>	60 dB(A)
<b>Voltage / Connection rating</b>	220 - 240V~ / 4.0 A
<b>Cooling system</b>	forced-air
<b>Defrost</b>	automatic
<b>Temperature range</b>	-9 °C to -35 °C <sup>2</sup>
<b>Gradient<sup>3</sup> / max. fluctuation<sup>4</sup></b>	2.9 °C / 3.6 °C
<b>External cabinet finish</b>	steel / white
<b>Door material</b>	steel
<b>Internal liner material</b>	304-grade stainless steel
<b>Type of control</b>	LED 7-segment display with buttons
<b>Power failure alarm</b>	immediately upon power failure for 72 hrs
<b>Fault: warning signal</b>	visual and audible
<b>Volt-free alarm contact</b>	yes
<b>Connectivity type</b>	SmartCoolingHub
<b>Connectivity solution</b>	Retrofittable
<b>Interface</b>	RS485
<b>Adjustable shelves</b>	4
<b>Shelf material</b>	wire shelves plastic-coated
<b>Usable shelf area in mm (w / d)</b>	533 / 650
<b>Shelf loading</b>	60 kg
<b>Castors</b>	castors with brake at the front, fixed castors at the rear
<b>Handle</b>	full-length integrated handle
<b>Type of lock</b>	mechanical
<b>Door hinges</b>	right, reversible on site
<b>Gross / net weight</b>	160 / 134 kg
<b>Accessories</b>	
<b>Shelf, plastic-coated</b>	7112393
<b>U-shaped trayslide, right</b>	9001761
<b>U-shaped trayslide, left</b>	9001757
<b>Foot pedal opener</b>	9590659
<b>SmartCoolingHub</b>	6125784
<b>Product temperature sensor</b>	9590407
<b>Side-by-Side set</b>	9901947

<sup>1</sup> Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.  
<sup>2</sup> The temperature range is valid at a maximum ambient temperature of +30°C

<sup>3</sup> Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.  
<sup>4</sup> Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.