



SFFsg 5501

Performance

Gross / net capacity	499 / 394 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	588 / 523 / 1388
Energy consumption in 365 days ¹	501 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	713 kJ/h
Refrigerant	R 290
Sound power level	49 dB(A)
Voltage / frequency	220 - 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 240 W
Cooling system	static
Defrost	manual
Temperature range	-9 °C to -30 °C
Gradient ² / max. fluctuation ³	6.0 °C / 2.9 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	commercial grade moulded polystyrene
Type of control	monochrome display, touch buttons
Power failure alarm	upon mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible	yes
Connectivity type	SmartModule
Connectivity solution	retrofittable
Interface	WiFi/LAN (optional)
Removable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	580 / 523
Shelf loading / Maximum total load	60 kg / 300 kg
Drawers / Number of baskets included	- / -
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	93 / 80 kg
Accessories	
Glass shelf / Full-depth drawer	9293495 / 9749825
Short bottom basket / Standard full-depth basket	9141004 / 9141791
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set in white	9017739
SmartModule	6145269



SFFsg 5501 ver. 740

Performance

Gross / net capacity	499 / 310 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	588 / 523 / 1388
Energy consumption in 365 days ¹	501 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	713 kJ/h
Refrigerant	R 290
Sound power level	49 dB(A)
Voltage / frequency	220 - 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 240 W
Cooling system	static
Defrost	manual
Temperature range	-9 °C to -30 °C
Gradient ² / max. fluctuation ³	6.0 °C / 2.9 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	commercial grade moulded polystyrene
Type of control	monochrome display, touch buttons
Power failure alarm	upon mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible	yes
Connectivity type	SmartModule
Connectivity solution	retrofittable
Interface	WiFi/LAN (optional)
Removable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	580 / 523
Shelf loading / Maximum total load	60 kg / 300 kg
Drawers	8 / 2
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	104 / 99 kg
Accessories	
Long drawer / Short drawer	9293495 / -
Glass shelf	- / -
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set in white	9017739
SmartModule	6145269



SFFsg 4001

Performance

Gross / net capacity	316 / 242 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	403 / 408 / 1588
Energy consumption in 365 days ¹	385 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	529 kJ/h
Refrigerant	R 290
Sound power level	49 dB(A)
Voltage / frequency	220 - 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 220 W
Cooling system	static
Defrost	manual
Temperature range	-9 °C to -30 °C
Gradient ² / max. fluctuation ³	5.7 °C / 2.5 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	commercial grade moulded polystyrene
Type of control	monochrome display, touch buttons
Power failure alarm	upon mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible	yes
Connectivity type	SmartModule
Connectivity solution	retrofittable
Interface	WiFi/LAN (optional)
Removable shelves	5
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	400 / 408
Shelf loading / Maximum total load	45 kg / 270 kg
Drawers	6
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	82 / 77 kg
Accessories	
Long drawer / Short drawer	9749823 / 9749844
Glass shelf	9293499
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set in white	9006786
SmartModule	6145269



SFFsg 4001 ver. 740

Performance

Gross / net capacity	316 / 190 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	403 / 408 / 1588
Energy consumption in 365 days ¹	385 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	529 kJ/h
Refrigerant	R 290
Sound power level	49 dB(A)
Voltage / frequency	220 - 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 220 W
Cooling system	static
Defrost	manual
Temperature range	-9 °C to -30 °C
Gradient ² / max. fluctuation ³	5.7 °C / 2.5 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	commercial grade moulded polystyrene
Type of control	monochrome display, touch buttons
Power failure alarm	upon mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible	yes
Connectivity type	SmartModule
Connectivity solution	retrofittable
Interface	WiFi/LAN (optional)
Removable shelves	5
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	400 / 408
Shelf loading / Maximum total load	45 kg / 270 kg
Drawers	6
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	87 / 82 kg
Accessories	
Long drawer / Short drawer	- / -
Glass shelf	9293499
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set in white	9006786
SmartModule	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers
² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.