Male Coupling, 1/2"





Technical Data

Item Number	0705
Couplings Size	1/2 "
Material	Chromium-plated brass
Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
FDA compliant raw material (CFR 21)	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
Use of phthalates and bisphenol A	No
Is Halal compliant	Yes
Box Quantity	1 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	3600 Pcs
Quantity Per Layer (Pallet)	0 Pcs.
Box Length	335 mm
Box Width	180 mm
Box Height	85 mm
Length	160 mm
Width	67 mm
Height	45 mm
Gross Weight	0,06 kg
Net Weight	0,05 kg
Cubik metre	0,0005 M3
Max. cleaning temperature (Dishwasher)	80 °C
Max usage temperature (non food contact)	70 °C
Min. usage temperature ³	-30 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	25 Bar
Gtin-13 Number	5705020007057
GTIN-14 Number (Box quantity)	15705020007054
Customs Tariff No.	74032100
Country of origin	Denmark

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.

^{**} Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead.