



New



New

SRTvh 1511

Perfection

Gross / net capacity	137 / 97 litre
Exterior dimensions in mm (w / d / h)	597 / 605 / 819
Interior dimensions in mm (w / d / h)	450 / 460 / 620
Energy consumption in 365 days ¹	187 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	208 kJ/h
Refrigerant	R 600a
Sound power level	45 dB(A)
Voltage / frequency	220 – 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 60 W
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.7 °C / 2.9 °C
External cabinet finish	steel / white
Door material / colour	Insulated glass door with plastic frame / white
Internal liner material	commercial grade moulded polystyrene
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution	integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	vertical LED light strip recessed in left wall with separate switch
Adjustable shelves / Shelf material	3 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	450 / 425
Shelf loading / Maximum total load	45 kg / 180 kg
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 12 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	45 / 43 kg

Accessories	
Worktop, white	9876118
White grid shelf	7113408
Pharmacy drawer	9876137
Perforated metal shelf, white	7746588
Castors / Adjustable legs	9904819 / 9906105
Scanner rail	7401607
Additional lock barrels (up to 5)	on request
Stacking kit, white	9876098
Side-by-Side set in white	9031901

SRTvh 1501

Perfection

Gross / net capacity	134 / 97 litre
Exterior dimensions in mm (w / d / h)	597 / 605 / 819
Interior dimensions in mm (w / d / h)	450 / 440 / 620
Energy consumption in 365 days ¹	111 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	198 kJ/h
Refrigerant	R 600a
Sound power level	43 dB(A)
Voltage / frequency	220 – 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 50 W
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.7 °C / 3.4 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	commercial grade moulded polystyrene
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution	integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED lighting column, left
Adjustable shelves / Shelf material	3 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	450 / 425
Shelf loading / Maximum total load	45 kg / 180 kg
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 12 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	37 / 33 kg

Accessories	
Worktop, white	9876118
White grid shelf	7113408
Perforated metal shelf, white	9876137
Castors / Adjustable legs	7746588
Scanner rail	9904819 / 9906105
Additional lock barrels (up to 5)	7401607
Stacking kit, white	on request
Side-by-Side set in white	9876098
SmartModule	9031901



New



New

SRTvg 1511

Performance

Gross / net capacity	137 / 97 litre
Exterior dimensions in mm (w / d / h)	597 / 605 / 819
Interior dimensions in mm (w / d / h)	450 / 460 / 620
Energy consumption in 365 days ¹	214 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	202 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / frequency	220 – 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 100 W
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.7 °C / 5.2 °C
External cabinet finish	steel / white
Door material / colour	Insulated glass door with plastic frame / white
Internal liner material	commercial grade moulded polystyrene
Type of control	monochrome display, touch buttons
Power failure alarm	upon mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution	retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	3 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	450 / 425
Shelf loading / Maximum total load	45 kg / 180 kg
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 12 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	45 / 43 kg

Accessories	
Worktop, white	9876118
White grid shelf	7113408
Perforated metal shelf, white	7746588
Castors / Adjustable legs	9904819 / 9906105
Scanner rail	7401607
Additional lock barrels (up to 5)	on request
Stacking kit, white	9876098
Side-by-Side set in white	9031901
SmartModule	6145269

SRTvg 1501

Performance

Gross / net capacity	134 / 97 litre
Exterior dimensions in mm (w / d / h)	597 / 605 / 819
Interior dimensions in mm (w / d / h)	450 / 440 / 620
Energy consumption in 365 days ¹	156 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	198 kJ/h
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / frequency	220 – 240V~ / 50 Hz
Connection rating / Rated consumption watts	2.0 A / 100 W
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	4.9 °C / 4.4 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	commercial grade moulded polystyrene
Type of control	monochrome display, touch buttons
Power failure alarm	upon mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution	retrofittable
Interface	WiFi/LAN (optional)
Interior light	
Adjustable shelves / Shelf material	3 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	450 / 425
Shelf loading / Maximum total load	45 kg / 180 kg
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 12 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	39 / 35 kg

Accessories	
Worktop, white	9876118
White grid shelf	7113408
Perforated metal shelf, white	7746588
Castors / Adjustable legs	9904819 / 9906105
Scanner rail	7401607
Additional lock barrels (up to 5)	on request
Stacking kit, white	9876098
Side-by-Side set in white	9031901
SmartModule	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers
² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.