



SRPvh 1412

Perfection

Gross / net capacity	1447 / 1091 litre
Exterior dimensions in mm (w / d / h)	1427 / 867 / 2135
Interior dimensions in mm (w / d / h)	976 / 638 / 1493
Energy consumption in 365 days ¹	705 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	695 kJ/h
Refrigerant	R 600a
Sound power level	60 dB(A)
Voltage / frequency	220 – 240V~ / 50/60 Hz
Connection rating / Rated consumption watts	4.0 A / 130 W
Cooling system / Defrost	forced-air / automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	2.6 °C / 1.9 °C
External cabinet finish	steel / white
Door material / colour	Insulating glass door with steel frame / white
Internal liner material	Chrome-nickel steel (1.4301 / AISI 304)
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs

Fault: warning signal / Volt-free alarm contact	visual and audible / yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution / Interface	integrated, removable / WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED light column both sides, separate connection

Adjustable shelves / Shelf material	8 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	480 / 638
Shelf loading / Maximum total load	60 kg / 520 kg
Castors	5 swivel castors, 2 with parking brake

Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
Type of lock	electronic, with remote control
Door hinges	left-hand / right-hand
Gross / net weight	293 / 268 kg

Accessories	
U-shaped trayslide, left / U-shaped trayslide, right	7745088 / 7745090
Grey grid shelf / Perforated metal shelf in grey	7112608 / 7746614
Castors Ø 100 mm	9597965
Adjustable feet, 115 – 175 mm	9080132
Foot pedal opener	9597649
Side-by-Side set in white	9597677
Additional remote controls / Digital input for electronic lock	6123395 / 9086958

SRPvh 1402

Perfection

Gross / net capacity	1391 / 1091 litre
Exterior dimensions in mm (w / d / h)	1427 / 867 / 2135
Interior dimensions in mm (w / d / h)	976 / 638 / 1493
Energy consumption in 365 days ¹	464 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	565 kJ/h
Refrigerant	R 600a
Sound power level	60 dB(A)
Voltage / frequency	220 – 240V~ / 50/60 Hz
Connection rating / Rated consumption watts	4.0 A / 130 W
Cooling system / Defrost	forced-air / automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	2.3 °C / 2.1 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	Chrome-nickel steel (1.4301 / AISI 304)
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs

Fault: warning signal / Volt-free alarm contact	visual and audible / yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution / Interface	integrated, removable / WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED light column both sides

Adjustable shelves / Shelf material	8 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	480 / 638
Shelf loading / Maximum total load	60 kg / 520 kg
Castors	5 swivel castors, 2 with parking brake

Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
Type of lock	electronic, with remote control
Door hinges	left-hand / right-hand
Gross / net weight	225 / 200 kg

Accessories	
U-shaped trayslide, left / U-shaped trayslide, right	7745088 / 7745090
Grey grid shelf / Perforated metal shelf in grey	7112608 / 7746614
Castors Ø 100 mm	9597965
Adjustable feet, 115 – 175 mm	9080132
Foot pedal opener	9597649
Side-by-Side set in white	9597677
Additional remote controls / Digital input for electronic lock	6123395 / 9086958



SRPvh 8411

Perfection

Gross / net capacity	903 / 702 litre
Exterior dimensions in mm (w / d / h)	787 / 1017 / 2135
Interior dimensions in mm (w / d / h)	579 / 788 / 1493
Energy consumption in 365 days ¹	374 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	425 kJ/h
Refrigerant	R 600a
Sound power level	60 dB(A)
Voltage / frequency	220 – 240V~ / 50/60 Hz
Connection rating / Rated consumption watts	4.0 A / 130 W
Cooling system / Defrost	forced-air / automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	3.9 °C / 2.9 °C
External cabinet finish	steel / white
Door material / colour	Insulating glass door with steel frame / white
Internal liner material	Chrome-nickel steel (1.4301 / AISI 304)
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs

Fault: warning signal / Volt-free alarm contact	visual and audible / yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution / Interface	integrated, removable / WiFi/LAN
Data logger	integrated, USB interface
Interior light	vertical LED light strip recessed in left wall with separate switch

Adjustable shelves / Shelf material	4 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	570 / 788
Shelf loading / Maximum total load	60 kg / 240 kg
Castors	castors with brake at the front, fixed castors at the rear

Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
Type of lock	electronic, with remote control
Door hinges	right, reversible on site
Gross / net weight	186 / 168 kg

Accessories	
U-shaped trayslide, left / U-shaped trayslide, right	7745092 / 7745094
Grey grid shelf / Perforated metal shelf in grey	7112614 / 7746616
Castors Ø 100 mm	9597828
Adjustable feet, 115 – 175 mm	9080131
Foot pedal opener	9597617
Side-by-Side set in white	9597677
Additional remote controls / Digital input for electronic lock	6123395 / 9086958

SRPvh 8401

Perfection

Gross / net capacity	871 / 702 litre
Exterior dimensions in mm (w / d / h)	787 / 1017 / 2135
Interior dimensions in mm (w / d / h)	579 / 788 / 1493
Energy consumption in 365 days ¹	220 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	360 kJ/h
Refrigerant	R 600a
Sound power level	60 dB(A)
Voltage / frequency	220 – 240V~ / 50/60 Hz
Connection rating / Rated consumption watts	4.0 A / 130 W
Cooling system / Defrost	forced-air / automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	3.1 °C / 2.3 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	Chrome-nickel steel (1.4301 / AISI 304)
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs

Fault: warning signal / Volt-free alarm contact	visual and audible / yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution / Interface	integrated, removable / WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED lighting column, left

Adjustable shelves / Shelf material	4 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	570 / 788
Shelf loading / Maximum total load	60 kg / 240 kg
Castors	castors with brake at the front, fixed castors at the rear

Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
Type of lock	electronic, with remote control
Door hinges	right, reversible on site
Gross / net weight	165 / 141 kg

Accessories	
U-shaped trayslide, left / U-shaped trayslide, right	7745092 / 7745094
Grey grid shelf / Perforated metal shelf in grey	7112614 / 7746616
Castors Ø 100 mm	9597828
Adjustable feet, 115 – 175 mm	9080131
Foot pedal opener	9597617
Side-by-Side set in white	9597677
Additional remote controls / Digital input for electronic lock	6123395 / 9086958

SRPvh 6511

Perfection

Gross / net capacity	642 / 480 litre
Exterior dimensions in mm (w / d / h)	697 / 867 / 2135
Interior dimensions in mm (w / d / h)	489 / 638 / 1493
Energy consumption in 365 days ¹	317 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	365 kJ/h
Refrigerant	R 600a
Sound power level	60 dB(A)
Voltage / frequency	220 – 240V~ / 50/60 Hz
Connection rating / Rated consumption watts	4.0 A / 130 W
Cooling system / Defrost	forced-air / automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	2.5 °C / 3.4 °C
External cabinet finish	steel / white
Door material / colour	Insulating glass door with steel frame / white
Internal liner material	Chrome-nickel steel (1.4301 / AISI 304)
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs

Fault: warning signal / Volt-free alarm contact	visual and audible / yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution / Interface	integrated, removable / WiFi/LAN
Data logger	integrated, USB interface
Interior light	vertical LED light strip recessed in left wall with separate switch

Adjustable shelves / Shelf material	4 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	480 / 638
Shelf loading / Maximum total load	60 kg / 240 kg
Castors	castors with brake at the front, fixed castors at the rear

Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
Type of lock	electronic, with remote control
Door hinges	right, reversible on site
Gross / net weight	169 / 152 kg

Accessories	
U-shaped trayslide, left / U-shaped trayslide, right	7745088 / 7745090
Grey grid shelf / Perforated metal shelf in grey	7112608 / 7746614
Castors Ø 100 mm	9597828
Adjustable feet, 115 – 175 mm	9080131
Foot pedal opener	9597617
Side-by-Side set in white	9597677
Additional remote controls / Digital input for electronic lock	6123395 / 9086958

SRPvh 6501

Perfection

Gross / net capacity	614 / 480 litre
Exterior dimensions in mm (w / d / h)	697 / 867 / 2135
Interior dimensions in mm (w / d / h)	489 / 638 / 1493
Energy consumption in 365 days ¹	172 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	305 kJ/h
Refrigerant	R 600a
Sound power level	60 dB(A)
Voltage / frequency	220 – 240V~ / 50/60 Hz
Connection rating / Rated consumption watts	4.0 A / 130 W
Cooling system / Defrost	forced-air / automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	2.3 °C / 2.5 °C
External cabinet finish	steel / white
Door material / colour	steel / white
Internal liner material	Chrome-nickel steel (1.4301 / AISI 304)
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs

Fault: warning signal / Volt-free alarm contact	visual and audible / yes
SmartMonitoring compatible / Connectivity type	yes / SmartModule
Connectivity solution / Interface	integrated, removable / WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED lighting column, left

Adjustable shelves / Shelf material	4 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	480 / 638
Shelf loading / Maximum total load	60 kg / 240 kg
Castors	castors with brake at the front, fixed castors at the rear

Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
Type of lock	electronic, with remote control
Door hinges	right, reversible on site
Gross / net weight	148 / 130 kg

Accessories	
U-shaped trayslide, left / U-shaped trayslide, right	7745088 / 7745090
Grey grid shelf / Perforated metal shelf in grey	7112608 / 7746614
Castors Ø 100 mm	9597828
Adjustable feet, 115 – 175 mm	9080131
Foot pedal opener	9597617
Side-by-Side set in white	9597677
Additional remote controls / Digital input for electronic lock	6123395 / 9086958

1 Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.
2 Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
3 Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.