



MKUv 1613
MediLine



MKUv 1610
MediLine



Gross / net capacity	152 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	408 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	5.1 °C / 4.9 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Number of shelves	4
Adjustable shelves	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	48 / 45 kg
Accessories	
Shelf, plastic-coated	7113333
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

Gross / net capacity	142 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	273 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	4.3 °C / 4.6 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Number of shelves	4
Adjustable shelves	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	42 / 39 kg
Accessories	
Shelf, plastic-coated	7113333
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



MKUv 1613 ver. H63
MediLine



MKUv 1610 ver. H63
MediLine



Gross / net capacity	152 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	369 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	4.1 °C / 1.5 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Number of shelves	1
Number of drawers	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	51 / 48 kg
Accessories	
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

Gross / net capacity	142 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	273 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	2.8 °C / 1.3 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Number of shelves	1
Number of drawers	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	45 / 42 kg
Accessories	
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.