



SRFfg 5501

Performance



Gross / net capacity	558 / 441 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	600 / 537 / 1460
Energy consumption in 365 days ¹	399 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	408 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.7 °C / 3.0 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	5
Shelf material	glass
Usable shelf area in mm (w / d)	600 / 537
Shelf loading / device	40 kg / 300 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
ATEX conformity	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	92 / 80 kg
Accessories	
Glass shelf	9291929
Perforated metal shelf	
Scanner rail	7435210
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



SRFfg 4001

Performance



Gross / net capacity	394 / 298 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 422 / 1660
Energy consumption in 365 days ¹	421 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	454 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	5.1 °C / 3.2 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	5
Shelf material	glass
Usable shelf area in mm (w / d)	460 / 422
Shelf loading / device	40 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
ATEX conformity	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	74 / 68 kg
Accessories	
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



SRFfg 3501

Performance



Gross / net capacity	344 / 261 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1684
Interior dimensions in mm (w / d / h)	460 / 537 / 1460
Energy consumption in 365 days ¹	406 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	388 kJ/h
Refrigerant	R 600a
Sound power level	48 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.6 °C / 3.1 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	4
Shelf material	glass
Usable shelf area in mm (w / d)	460 / 537
Shelf loading / device	40 kg / 180 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
ATEX conformity	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	70 / 60 kg
Accessories	
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269